- 1. (Currently Amended) A textile label featuring
- a textile base layer (2),
- a transponder arrangement that is bonded to the textile base layer (2) by means of a first adhesive layer (3), and
- a second adhesive layer (4), and
- an additional textile layer consisting of an upper label (7) bonded to the remainder of the label by means of the second adhesive layer (4), wherein the transponder arrangement features an antenna (6) and at least one electronic component that is sealed against environmental influences including one of water, suds, chemical cleaning agents and heat by means of the first and the second adhesive layer (3, 4).
- 2. (Previously Amended) The textile label according to claim 1, wherein at least one electronic component includes a chip (5).
- 3. (Previously Amended) The textile label according to claim 1, wherein the second adhesive layer (4) extends over the entire transponder arrangement in a plane fashion.
- 4. (Previously Amended) The textile label according to claim 1, wherein the first adhesive layer (3) consists of a polyester adhesive.
- 5. (Previously Amended) The textile label according to claim 1, wherein the second adhesive layer (4) consists of a hot-melt adhesive.
- 6. (Previously Amended) The textile label according to claim 1, wherein the antenna (6) consists at least predominantly of copper.
- 7. (Previously Amended) The textile label according to claim 1, wherein the base layer (2) features at least one of the group consisting of graphic and alphanumeric symbols.

- 10. (Currently Amended) The textile label according to claim  $9 \frac{1}{1}$ , wherein the upper label (7) features at least one of the group consisting of graphic and alphanumeric symbols.
- 11. (Currently Amended) The textile label according to claim  $9\,\underline{1}$ , wherein the upper label (7) protrudes over the base layer (2) on at least one side.
- 12. (Original) The textile label according to claim 11, wherein at least a portion of the region (8, 8a) of the upper label (7) that protrudes over the base layer (2) can be separated from the remainder of the label.
- 13. (Previously Amended) The textile label according to one of claim 11, wherein the region (8, 8a) of the upper label (7) that protrudes over the base layer (2) is sewn to a garment.
- 14. (Previously Amended) The textile label according to one of claim 11, wherein the region (8, 8a) of the upper label (7) that protrudes over the base layer (2) is bonded to a garment.
- 15. (Currently Amended) The textile label according to claim  $\frac{8}{1}$ , wherein the additional textile layer consists of part of a garment.
- 16. (Previously Amended) A garment featuring a label according to claim 1.
- 17. (Withdrawn) A method for manufacturing a textile label comprising at least the following steps
- applying a first adhesive layer (3) on a textile base layer (2),
- attaching a transponder arrangement featuring an antenna (6) and at least one additional electronic component (5) to the first adhesive layer (3) and
- applying a second adhesive layer (4) such that it covers and seals at least the additional electronic component (5).

- 18. (Withdrawn) The method according to claim 17, wherein the second adhesive layer (4) is applied such that it covers the entire transponder arrangement.
- 19. (Withdrawn) The method according to claim 17, wherein the attachment of the transponder arrangement consists of bonding on a metal foil section and subsequently etching the antenna (6) out of the metal foil section.
- 20. (Withdrawn) The method according to claim 19, wherein a metal foil section is used that predominantly consists of copper.
- 21. (Withdrawn) The method according to claims 17, wherein the first adhesive layer (3) is produced with polyester adhesive.
- 22. (Withdrawn) The method according to claims 17, wherein the second adhesive layer (4) is produced with hot-melt adhesive.
- 23. (Withdrawn) The method according to one of claims 17, wherein the bonding to an additional textile layer is realized with the aid of the second adhesive layer (4).
- 24. (Withdrawn) A method for labeling a garment, wherein a label according to claims 1, is attached to a garment by one of the group of procedures consisting of sewing and bonding.